



SERIES 115, 1000 BAR

High-Pressure Hydraulic Products, Couplings & Nipples



Technical data

Nominal flow diameter:	2.5 mm (3/32")
Flow capacity:	6.0 l/min
Max. working pressure:	1000 Bar
Min. burst pressure:	2600 Bar
Temperature range:	-30°C - +100°C
Material coupling:	Hardened, zinc chromate plated steel
Material nipple	Hardened, zinc chromate plated steel
Material seal:	Nitrile (NBR) other sealing materials on request

Flow capacity is measured at 4 Bar pressure drop

Coupling	Part No.	Connection	Rec. seal method
Female thread	10 115 1201	G 1/8"	T1
	10 115 1202	G 1/4"	CMS
	10 115 1204	G 3/8"	T3
	10 115 1401	1/8" NPT	-
	10 115 1402	1/4" NPT	-
	10 115 1404	3/8" NPT	-
Female thread	10 115 1222	G 1/4"	CMS
(With safety lock)	10 115 1422	1/4" NPT	-
Nipples	Part No.	Connection	Rec. seal method
Female thread	10 115 6201	G 1/8"	T1
	10 115 6202	G 1/4"	CMS
	10 115 6204	G 3/8"	T3
	10 115 6401	1/8" NPT	-
	10 115 6402	1/4" NPT	-
	10 115 6404	3/8" NPT	-

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th