



## SERIES 116, 1500 BAR

### High-Pressure Hydraulic Products, Couplings & Nipples



#### Technical data

Nominal flow diameter:	2.5 mm (3/32")
Flow capacity:	6.0 l/min
Max. working pressure:	1500 Bar
Min. burst pressure:	3000 Bar
Temperature range:	-30°C - +100°C
Material coupling:	Hardened, zinc chromate plated steel
Material nipple	Hardened, zinc chromate plated steel
Material seal:	Nitrile (NBR) other sealing materials on request

*Flow capacity is measured at 4 Bar pressure drop*

Coupling	Part No.	Connection	Rec. Seal method
Female thread	10 116 1202	G 1/4"	CMS
	10 116 1402	1/4" NPT	-
	(With angled conn)	10 116 1230	G1/4"
	10 116 1250	G 1/4"	CMS
(With safety lock)	10 116 1422	1/4" NPT	-
	10 116 1222	G 1/4"	CMS
	10 116 1246	G 1/4"	CMS
Nipple	Part No.	Connection	Rec. Seal method
Female thread	10 116 6202	G 1/4"	CMS
	10 116 6402	1/4" NPT	-
	10 116 6241	G 1/4"	CMS

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

#### Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th