



SERIES 125, 2000 / 2500 BAR

High-Pressure Hydraulic Products, Couplings & Nipples



- High working pressure
- Compact design and unique sealing design
- Non-drip on connection and disconnection

Series 125 is a CEJN original with extremely small outside dimensions and a patented seal design, making it ideal for bolt tensioners, bearing pullers and other applications. All exposed components are made of zinc-plated steel. Like all products featured in the CEJN High-Pressure range, non-drip connection and disconnection are standard. Plastic dust caps are also standard on the couplings and nipples, a feature that extends the service life of the entire hydraulic system.

Technical data

Nominal flow diameter:	2.5 mm (3/32")
Flow capacity:	5.8 l/min
Max. working pressure:	2000 / 2500 Bar
Min. burst pressure:	4000 / 5000 Bar
Temperature range:	-30°C - +100°C
Material coupling:	Hardened, zinc-nickel, zinc-iron
Material nipple	Hardened, zinc-nickel
Material seal:	Nitrile (NBR) other sealing materials on request

Flow capacity is measured at 4 Bar pressure drop

Series 125, 2000 Bar		Part No.	Connection	Rec. Seal method
Couplings	Female thread	10 125 1202	G 1/4"	CMS
	Male thread	10 125 5252	G 1/4"	W
Nipples	Female thread	10 125 6202	G 1/4"	CMS
Series 125, 2500 Bar		Part No.	Connection	Rec. Seal method
Couplings	Female thread	10 125 1203	G 1/4"	CMS
	Female thread with 90° angle	10 125 1248	G 1/4"	CMS
Nipples	Female thread	10 125 6203	G 1/4"	CMS

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimit Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th