



SERIES 232

High-Pressure Hydraulic Products, Screw-to-Connect Couplings & Nipples

Series 232 is a screw-to-connect Series and a good complement to CEJN's large range of quick connect couplings. It is also characterised by CEJN's quality approach and has a high flow rate capacity. The Series can be connected under pressure and is interchangeable with most screw-to-connect couplings. Hand pumps, cylinders and jacks are just a few examples of application areas.



Technical data

Nominal flow diameter:	6.3 mm (1/4") & 10 mm (3/8")
Flow capacity:	16.1 - 21.2 l/min
Max. working pressure:	720 Bar
Min. burst pressure:	2160 Bar
Temperature range:	-30°C - +100°C
Material coupling:	Zinc plated steel
Material nipple	Zinc plated steel
Material seal:	Nitrile (NBR)

Flow capacity is measured at 4 Bar pressure drop

Couplings	Part No.	Connection	Length	Diameter	Torque (Nm)
Female thread	10 232 1402	NPT 1/4"	56 mm	30 mm	50 - 60
	10 232 1404	NPT 3/8"	66 mm	35 mm	70 - 80
Male thread	10 232 1452	NPT 1/4"	53 mm	30 mm	50 - 60
	10 232 1484	NPT 3/8"	62 mm	35 mm	70 - 80

Nipples	Part No.	Connection	Length	Diameter	Torque (Nm)
Female thread	10 232 6402	NPT 1/4"	39 mm	30 mm	50 - 60
	10 232 6434	NPT 3/8"	40.5 mm	35 mm	70 - 80

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimit Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th