



## MULTI-X RANGE

### Hydraulic Products, Multi-X

- Compact design
- Great flexibility and high performance
- Easy and ergonomic to maneuver - perpendicular lever movement
- Self-aligning hose connectors



CEJN Multi-X is a multi-connection plate with 2, 4 and 6 ports. All plates are designed with non-drip Flat-Face couplings according to ISO 16028. Nipples with integrated pressure eliminators ensure smooth connections even with high residual pressure. Working pressure of up to 350 Bar can be used on half the ports simultaneously with the other half of the ports used as return lines with a maximum pressure of 50 Bar. For optimal flexibility both the male and female plate can be used as the fixed part and each plate can also be outfitted with electric connectors.

### Technical data

<b>Max. working pressure:</b>	350 Bar (5076 PSI)
<b>Min. burst pressure:</b>	1200 Bar (17405 PSI)
<b>Temperature range:</b>	-30°C - +100°C
<b>Material female plate:</b>	Zinc plated steel, anodised aluminium, zinc, brass
<b>Material male plate:</b>	Zinc plated steel, anodised aluminium, brass
<b>Material seal:</b>	NBR/PUR

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

### Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th