



## SERIE 359 PRESS CHECK

### Hydraulic Products, Press-Check Screw to Connect

- The most common test point system in the world
- Test point, mini hose and couplings for monitoring and testing of circuits in mobile and hydraulics equipment
- For work pressures up to 630 Bar (9137 PSI)
- Offer a simple and inexpensive way to check the pressure in your hydraulic system



The test point nipples for the Press-Check system are available with plastic or metal dust caps and comes in four different sealing types; metal to metal seal, sealing by fitted ring, sealing by thread and sealing by O-ring.

Press-Check Monitoring System for hydraulics consists of a wide range of test points, mini hose and couplings for monitoring and testing of circuits in mobile and hydraulic equipment. It can be installed at any point of the hydraulic system where pressures needs to be monitored. The system is designed and manufactures according to ISO 15171-2 and is fully interchangeable with several other brands.

### Technical data

Temperature range:	-20°C - +100°C
Material nipple:	Zinc-plated steel
Material seal:	Nitrile (NBR)

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

### Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th