



SERIES 315 eSafe MULTI-LINK

Pneumatic Products, Multi-Link Systems

- Compact multiple vented safety outlets
- Ready-made units, no assembly necessary
- Outlets adjustable up to 180°

With multiple outlets Series 315 eSafe Multi-Link offers both flexibility and high performance. It is a one hand operated safety coupling that vents before disconnection eliminating the risk of hose whip. Available in 1- to 5-outlet units. A small unit can be expanded with extensions to create a larger unit with up to five outlets. Separate units can easily be connected. Combine with CEJN polyurethane hose and FRL units to create a safe and flexible high performance air distribution system. Series 315 eSafe Multi-Link complies with ISO Standard 4414 and EN 983. It offers standard features; one-hand operated, high flow and long service life.



Technical data

Nominal flow diameter:	7.5 mm (5/16")
Max. working pressure:	16 bar (232 PSI)
Min. burst pressure:	64 bar (928 PSI)
Temperature range:	-20°C - +100°C
Material:	Zinc-plated steel/zinc
Media:	Compressed air, neutral gas
Connection:	G 1/2" Female thread

Serie 315 eSafe	Part No.	Connection
Extension Unit	19 902 9150	G 1/2"
1 Outlet unit	19 902 9151	G 1/2"
2 Outlet unit	19 902 9152	G 1/2"
3 Outlet unit	19 902 9153	G 1/2"
4 Outlet unit	19 902 9154	G 1/2"

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We reserve the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th