



## SPIRAL HOSE

### Pneumatic Products, Non-Braided Hose

- Light and flexible
- Excellent resistance to oil and solvents
- Long service life with outstanding again qualities

CEJN spiral hose is an excellent choice for applications that call for hose to have excellent recoil ability and crimp resistance. It offer high tensile and tear strength and resistance to impacts. The hose is abrasion resistant and is suitable for applications in a wide temperature range.

#### Technical data

<b>Size (ID x OD mm)</b>	5x8, 6.5x10, 8x12, 11x16
<b>Hose material:</b>	FDA approved, Ester-based polyurethane
<b>Max. working pressure:</b>	10 Bar (145 PSI)
<b>Min. burst pressure:</b>	25 Bar (362 PSI)

Spiral Hose	ID x OD (mm)	Part No.	Service Length (M)	Total length (M)
2 Meter	5 x 8	19 958 5820	2.0	2.5
	6.5 x 10	19 958 6020	2.0	2.5
	8 x 12	19 958 6220	2.0	2.5
	11 x 16	19 958 6620	2.0	2.5
4 Meter	5 x 8	19 958 5840	4.0	5.0
	6.5 x 10	19 958 6040	4.0	5.0
	8 x 12	19 958 6240	4.0	5.0
	11 x 16	19 958 6640	4.0	5.0
6 Meter	5 x 8	19 958 5860	6.0	7.5
	6.5 x 10	19 958 6060	6.0	7.5
	8 x 12	19 958 6260	6.0	7.5
	11 x 16	19 958 6660	6.0	7.5
8 Meter	5 x 8	19 958 5880	8.0	10.0
	6.5 x 10	19 958 6080	8.0	10.0
	8 x 12	19 958 6280	8.0	10.0
	11 x 16	19 958 6680	8.0	10.0

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

#### Chalongchai Lohakit Ltd., Part. Head Office

75 Trimuth Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th