



## STRAIGHT BRAIDED PUR HOSE

### Pneumatic Products, Hose

- Light and flexible
- Excellent resistance to oil and solvents
- Long service life with outstanding again qualities

CEJN straight braided hose is an excellent choice for applications requiring a maximum working pressure up to 16 bar (232 PSI). It offers a wide temperature range and high tensile, tear, and impact strength. The hose easily springs back to its original form and has excellent abrasion resistance.

### Technical data

Hose material: Ester-based polyurethane reinforce with polyester fiber

Straight Braided Hose	ID x OD	Total length	Part No.	Max. working pressure	Burst pressure
	6.5 x 10 mm	100	19 958 1000	16 bar (232 PSI)	64 bar (928 PSI)
	8 x 12 mm	100	19 958 1200	16 bar (232 PSI)	64 bar (928 PSI)
	9.5 x 13.5 mm	100	19 958 1350	16 bar (232 PSI)	64 bar (928 PSI)
	11 x 16 mm	100	19 958 1600	12 bar (174 PSI)	48 bar (696 PSI)
	13 x 18 mm	50	19 958 1801	10 bar (145 PSI)	40 bar (580 PSI)

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

### Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th