



STRAIGHT NON-BRAIDED PUR HOSE

Pneumatic Products, Hose

- Suitable for push-to-connect fitting
- Excellent resistance to oil and solvents
- Long service life with outstanding again qualities



CEJN non-braided hose is an excellent choice for applications requiring a maximum working pressure up to 10 bar (145 PSI). It is light and flexible and offers high tensile, tear, and impact strength. The hose easily springs back to its original form.

Technical data

Hose material: FDA approved, Ester-based polyurethane

| Straight Non-Braided Hose | ID x OD | Total length | Part No. | Max. working pressure | Burst pressure |
|---------------------------|-------------|--------------|-------------|-----------------------|------------------|
| | 4 x 6 mm | 50 | 19 958 0702 | 10 bar (145 PSI) | 25 bar (362 PSI) |
| | 5 x 8 mm | 50 | 19 958 0802 | 10 bar (145 PSI) | 25 bar (362 PSI) |
| | 6.5 x 10 mm | 50 | 19 958 1002 | 10 bar (145 PSI) | 25 bar (362 PSI) |
| | 8 x 12 mm | 50 | 19 958 1202 | 10 bar (145 PSI) | 25 bar (362 PSI) |
| | 11 x 16 mm | 50 | 19 958 1602 | 10 bar (145 PSI) | 25 bar (362 PSI) |

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th