

## **COMPRESSED AIR HOSE REELS**

## Pneumatic Products, Hose & Cable Reels

- High flow capacity
- Low pressure drop
- Strong and durable



CEJN Hose Reels for compressed air feature high-quality, oil-resistant polyurethane hose. The feeder hose connection, axle and swivel design ensures a high flow rate and low pressure drop, securing top performance. The reel and spring assembly is tested to endure hours of hard use. The reels can swivel 300° making it possible for the operator to move around freely and the low pulling force makes it easy for anyone to handle. The impact resistant casing protects the hose and reel mechanism from dirt and debris. The Quick-Locks on the mounting bracket makes installation and service quick and easy. The Hose Reels are available in several casing sizes and hose dimensions, as well as with CEJN braided anti-spark hose. All hose reels are supplied with a feeder hose.

## Technical data

Feeder hose length:	2 m (6.6 ft)
Hose material:	Braided PUR
Connections:	Male thread
Temperature range:	-20°C - +60°C

Hose & cable reel	Part No.	ID x OD	Connection	Reel diameter	Max working pressure
10 meters	19 911 5130	11 x 16	R 1/2"	430 mm	12 bar (174 PSI)
14 meters	19 911 5120	9.5 x 13.5	R 1/4"	430 mm	12 bar (174 PSI)
16 meters	19 911 5100	8 x 12	R 1/4"	430 mm	12 bar (174 PSI)

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

## Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th