



SERIES 210, MULTIFLOW GUN

Pneumatic Products, Air & fluid gun

- Unmatched blowing force
- Adjustable flow control
- Ergonomical, non-slip grip

CEJN's MultiFLOW blowgun effectively cleans surfaces with air or water with unparalleled blowing force. Precise flow is achieved by adjustable flow settings. Nozzle adjusts from narrow jet to wide beam. The MultiFLOW meets and exceeds OSHA safety standards when dead-ended.



Technical data

Material blowgun:	POM, TPE, Aluminum
Media:	Air and non-explosive water based liquids
Material seal:	NBR (Nitrile)
Max. working pressure:	16 bar (232 bar)
Min. burst pressure:	64 bar (928 bar)
Temperature range:	60°C - +80°C @10 bar working pressure
Temperature range:	-20°C - +60°C @16 bar working pressure

Flow capacity is measured at 6 bar (87 PSI) inlet pressure.

MultiFLOW	Connection	Part No.	Air flow min-max	Fluid flow min-max	Sound level
Adjustable jet	Adapter 1/4"	11 210 0450	200 - 1200 l/min	5 l/min - 25 l/min	79 dB - 101 dB
Straight tube 90	G 1/4" Brass	11 210 0152	150 - 1100 l/min	-	-
Star-tip tube 90	G 1/4" Brass	11 210 3152	100 - 1100 l/min	-	-
Adjustable fluid	G 1/4" Brass	11 210 0352	-	3.5 l/min - 15 l/min	-
8 Pack display	Adapter 1/4"	11 210 9981	200 - 1200 l/min	5 l/min - 25 l/min	79 dB - 101 dB

Check with an authorised Chalongchai Lohakit distributor for availability and prices. We are reserves the right to make changes with our further notification.

Chalongchai Lohakit Ltd., Part. Head Office

75 Trimith Rd., Samphantawong, Samphantawong, Bangkok 10100 THAILAND

Tel: +66 (0) 2233 0403, 0 2233 5987 Fax: +66 (0) 2233 3713 Email: sales@chalongchai.co.th